Characterization of Alternan, a high molar mass polysaccharide from *Leuconostoc mesenteroides*, by aFFFF-MALS

Jeffrey A. Ahlgren¹ and Gregory L. Côté ²




¹Wyatt Technology Corporation, Santa Barbara, CA 93117

²National Center for Agricultural Utilization Research, USDA/ARS, Peoria, IL 61604

ABSTRACT: Native alternan is a high molar mass polysaccharide produced by some strains of the bacterium *Lueconostoc mesenteroides*. It consists of D-glucose units that alternate their linkages between alpha-(1-6) and alpha-(1-3) between glucosyl moieties. The glucose units contained in the polysaccharide are derived from the hydrolysis of sucrose in a reaction catalyzed by the enzyme alternan sucrase. The native polymer can be produced *in vivo* by the intact bacterial culture or *in vitro* with cell-free supernatant containing alternan sucrase plus sucrose. The polysaccharide can be purified from cell-free supernatant by several rounds of alcohol precipitation. In this study we used the Wyatt Eclipse Field Flow Fractionation System (aFFFF) to fractionate the polysaccharide and multi-angle light scattering (MALS) coupled with a refractive index detector to measure the molar mass and size of native alternan and compared these results to traditional SEC-MALS. The results show that native alternan was highly polydisperse, with a weight average molar mass of 50 million Da and an RMS radius of 45 nm. Conformation analysis showed the structure of the polysaccharide to be a random coil. The RMS radius measured by MALS was compared to the hydrodynamic radius (Rh) of the polysaccharide as measured by batch dynamic light scattering (DLS) using the Wyatt DynaPro detector; DLS analysis revealed an R_h of 50 nm that was stable from 25-85°C.

Alternan



Wyatt


echnology

Materials and Methods:

Purified Alternan was prepared in 100 mM NaNO3 containing 0.02% (w/v) sodium azide as a preservative. It was filtered through a 0.45 um syringe filter prior to use. For both FFF-MALS and SEC-MALS, the mobile phase was also NaNO3/NaN3. For analysis of Mw and RMS radius, a Wyatt DAWN HELEOS and Wyatt Optilab rEX were used for detection.

The Wyatt Eclipse aFFFF






The chemical structure of Alternan

The Wyatt Eclipse 3 utilized the 18-cm channel equipped with a 10 kDa MWCO, regenerated cellulose membrane with a 350 um tall spacer. The channel flow rate was 1 ml/min. During elution, the cross flow was initially set at 1.0 ml/min, and a 50 minute linear gradient to 0 ml/min cross flow was used.


For SEC-MALS, a Shodex SB-807-HQ column equilibrated with the same NaNO3/NaN3 mobile phase was used. The flow rate was constant at 0.5 ml/min.

For DLS measurement, a Wyatt DynaPro Temperature-controlled Microsampler and cuvette were used. The initial temperature was 25° C, and the R_h measured at 10° C intervals to 85° C.

FFF-MALS of Alternan




SEC-MALS of Alternan




aFFFF-MALS vs. SEC-MALS

molar mass vs. volume

(lom/g)





Batch DLS Analysis

Conclusions:

The separation of Alternan, a highly polydisperse polysaccharide, was more effective by aFFFF than SEC on a Shodex 807 column. The FFF separation was more uniform and eliminated the small trailing peak seen by SEC separation on the Shodex SB-807 column. The conformation plot produced by the aFFFF separation resulted in a slope of 0.62, which is typical of a random coil formation. The same plot produced by the SEC separation resulted in a slope of 0.44, which suggests a more compact structure. Additional experimentation will be needed to resolve the discrepancy between these two methods.

DLS analysis showed that the R_h of the Alternan was very temperature stable at 50 nm; there was no change in the size of the molecule from 25-85°C (the highest temperature tested).

Copyright 2007 Wyatt Technology Corporation. All Rights Reserved.